Safety Data Sheets

Atera Reagent Kits

Atera Cell Segmentation Reagents, PN-1001146

Reagents	PNs
Atera Block and Stain Buffer	2001945
Atera Multi-Tissue Stain	2001946
Atera Signal Booster	2001947

Atera Block and Stain Buffer

10x Genomics, Inc.

Part Number: **2001945**
Version No: **1.1**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **04/06/2026**
Revision Date: **25/06/2026**
Print Date: **25/06/2026**
S.GHS.USA.EN.B

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Atera Block and Stain Buffer
Synonyms	Not Available
Other means of identification	2001945

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Professional Users Only

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**10x Genomics, Inc.**
Address	6230 Stoneridge Mall Rd, Pleasanton, California, 94588, United States of America
Telephone	+1 925 401 7300
Fax	NA
Website	www.10xgenomics.com
Email	info@10xgenomics.com

Emergency phone number

Association / Organisation	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	**+49 32 211121704**
Other emergency telephone number(s)	**+61 3 9573 3188**

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

Classification	Non hazardous

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Page 1 continued...

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9005-49-6	5-10	heparin
9005-64-5	1-5	sorbitan monolaurate, ethoxylated

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: • Flush skin and hair with running water (and soap if available). • Seek medical attention in event of irritation.
Inhalation	• If fumes, aerosols or combustion products are inhaled remove from contaminated area. • Other measures are usually unnecessary.
Ingestion	• If swallowed do **NOT** induce vomiting. • If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. • Observe the patient carefully. • Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. • Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. • Seek medical advice.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
· The use of low molecular weight heparins (LMWHs) should be avoided in patients with known allergies to LMWHs, heparin, sulfites or benzyl alcohol, in patients with active major bleeding, or patients with a history of heparin-induced low blood platelet count (also known as heparin-induced thrombocytopenia or HIT).
· High treatment doses are contraindicated in acute bleedings such as cerebral or gastrointestinal haemorrhage. LMWHs are more dependent on renal function for their excretion than unfractionated heparin so their biological half-life may be prolonged in patients with kidney failure and therefore their use in the setting of creatinine clearance rate (CrCl) <30 mL/min may need to be avoided. Apart from using unfractionated heparin instead, it may be possible to reduce the dose and/or monitor the anti-Xa activity to guide treatment.
· LMWHs should be used with extreme caution in patients undergoing any procedure involving spinal anaesthesia/puncture, in conditions with increased risk of bleeding or in patients with a history of heparin-induced thrombocytopenia
Antidote
In clinical situations in which the antithrombotic effect of LMWHs needs to be neutralized, protamine is used to neutralize heparin by binding to it. Studies in animals and in vitro studies have demonstrated that protamine neutralizes the antithrombin activity of LMWHs, normalizing the aPTT and thrombin time. However, protamine appears to only partially neutralize the anti-factor Xa activity of LMWH. Because the molecular weight of heparin impacts its interaction with protamine, it is likely that the lack of complete neutralization of anti-factor Xa is due to a reduced protamine binding to the LMWHs moieties in the preparation. Protamine is a medicine that requires a high level of caution when used

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Continued...

Special protective equipment and precautions for fire-fighters

Fire Fighting	• Alert Fire Brigade and tell them location and nature of hazard. • Wear full body protective clothing with breathing apparatus. • Prevent, by any means available, spillage from entering drains or water course. • Use water delivered as a fine spray to control fire and cool adjacent area. • Avoid spraying water onto liquid pools. • **DO NOT** approach containers suspected to be hot. • Cool fire exposed containers with water spray from a protected location. • If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	• Combustible. • Slight fire hazard when exposed to heat or flame. • Heating may cause expansion or decomposition leading to violent rupture of containers. • On combustion, may emit toxic fumes of carbon monoxide (CO). • May emit acrid smoke. • Mists containing combustible materials may be explosive. Combustion products include: • carbon dioxide (CO_2) • other pyrolysis products typical of burning organic material. May emit poisonous fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	• Remove all ignition sources. • Clean up all spills immediately. • Avoid breathing vapours and contact with skin and eyes. • Control personal contact with the substance, by using protective equipment. • Contain and absorb spill with sand, earth, inert material or vermiculite. • Wipe up. • Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • No smoking, naked lights or ignition sources. • Increase ventilation. • Stop leak if safe to do so. • Contain spill with sand, earth or vermiculite. • Collect recoverable product into labelled containers for recycling. • Absorb remaining product with sand, earth or vermiculite. • Collect solid residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • If contamination of drains or waterways occurs, advise emergency services.

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Workers in many different occupations are at risk of exposure to bloodborne pathogens. First Responders, First aid team members, housekeeping personnel in some settings, and nurses are examples of workers who may be at risk of exposure. In the USA, the Federal Occupational Safety & Health Administration (OSHA) issued the “Occupational Exposure to Bloodborne Pathogens Standard (29 CFR 1910.1030)”. Federal OSHA determined that employees have a significant health risk as the result of occupational exposure to blood and other potentially infectious materials (OPIM) because they may contain bloodborne pathogens. These pathogens include, but are not limited to: hepatitis B virus (HBV), hepatitis C virus (HCV), and HIV (human immunodeficiency virus). Each employer who has an employee(s) with occupational exposure to blood or or other potentially infectious material (OPIM) is required to document an exposure determination. The exposure determination is made without regard to the use of personal protective equipment since employees are considered exposed even if they wear personal protective equipment. The exposure determination requires employers to identify and document: 1) those job classifications in which all employees have occupational exposure, and 2) those job classifications in which some employee have occupational exposure. In the latter case, specific tasks and procedures, or groups of closely related tasks and procedures, which are associated with occupational exposure, must be delineated. (Note: Employees expected as part of their job duties to render first aid or medical assistance are covered by the requirements of the standard. If the employee is not designated nor trained in first aid but is still expected to render first aid to an injured employee or customer/client, this expectation would constitute, in affect, an actual designation of the employee and OSHA would require such employee to be enrolled in a bloodborne pathogen program. The standard excludes employees who perform unanticipated “Good Samaritan” acts; e.g. one employee may assist another who has a nosebleed or is bleeding as result of a fall. This would not be considered an occupational exposure unless the employee who provides assistance is expected to render medical assistance as one of his/her job duties.) • Avoid skin contact, including inhalation. • Wear protective clothing when risk of exposure occurs. • Use in a well-ventilated area. • Prevent concentration in hollows and sumps. • **DO NOT** enter confined spaces until atmosphere has been checked. • **DO NOT** allow material to come in direct contact with human skin or eyes.

Continued...

	• **DO NOT** allow material to come in contact with exposed food or food contact surfaces. • Suitable PPE must be worn at all times. • Avoid contact with incompatible materials. • When handling, **DO NOT** eat, drink or smoke. • Keep containers securely sealed when not in use. • Avoid physical damage to containers. • Always wash hands with soap and water after handling. • Work clothes should be laundered separately. Launder contaminated clothing before re-use. • Use good occupational work practice. • Observe manufacturer's storage and handling recommendations contained within this SDS. • Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	• Store in original containers. • Keep containers securely sealed. • No smoking, naked lights or ignition sources. • Store in a cool, dry, well-ventilated area. • Store away from incompatible materials and foodstuff containers. • Protect containers against physical damage and check regularly for leaks. • Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	• Glass container is suitable for laboratory quantities • Metal can or drum • Packaging as recommended by manufacturer. • Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Dilute solutions of all sugars are subject to fermentation, either by yeast or by other microorganisms or enzymes derived from these, producing gases which can pressurise and burst sealed containers. Some microorganisms will produce hydrogen or methane, adding a fire and explosion hazard. • Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	TEEL-1	TEEL-2	TEEL-3
Atera Block and Stain Buffer	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
heparin	Not Available	Not Available
sorbitan monolaurate, ethoxylated	Not Available	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
heparin	C	> 0.1 to ≤ 1 milligrams per cubic meter of air (mg/m³)
Notes:	***Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.***	

Exposure controls

Appropriate engineering controls

Enclosed local exhaust ventilation is required at points of dust, fume or vapour generation.
HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapours.
Barrier protection or laminar flow cabinets should be considered for laboratory scale handling.
A fume hood or vented balance enclosure is recommended for weighing/ transferring quantities exceeding 500 mg.
When handling quantities up to 500 gram in either a standard laboratory with general dilution ventilation (e.g. 6-12 air changes per hour) is preferred. Quantities up to 1 kilogram may require a designated laboratory using fume hood, biological safety cabinet, or approved vented enclosures. Quantities exceeding 1 kilogram should be handled in a designated laboratory or containment laboratory using appropriate barrier/ containment technology.
Manufacturing and pilot plant operations require barrier/ containment and direct coupling technologies.
Barrier/ containment technology and direct coupling (totally enclosed processes that create a barrier between the equipment and the room) typically use double or split butterfly valves and hybrid unidirectional airflow/ local exhaust ventilation solutions (e.g. powder containment booths). Glove bags, isolator glove box systems are optional. HEPA filtration of exhaust from dry product handling areas is required.
Fume-hoods and other open-face containment devices are acceptable when face velocities of at least 1 m/s (200 feet/minute) are achieved.
Partitions, barriers, and other partial containment technologies are required to prevent migration of the material to uncontrolled areas. For non-routine emergencies maximum local and general exhaust are necessary. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, etc. evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents

Continued...

	<table><tr><td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr></table> Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2.5 m/s (200-500 f/min.) for extraction of gases discharged 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. The need for respiratory protection should also be assessed where incidental or accidental exposure is anticipated: Dependent on levels of contamination, PAPR, full face air purifying devices with P2 or P3 filters or air supplied respirators should be evaluated. The following protective devices are recommended where exposures exceed the recommended exposure control guidelines by factors of: 10; high efficiency particulate (HEPA) filters or cartridges 10-25; loose-fitting (Tyvek or helmet type) HEPA powered-air purifying respirator. 25-50; a full face-piece negative pressure respirator with HEPA filters 50-100; tight-fitting, full face-piece HEPA PAPR 100-1000; a hood-shroud HEPA PAPR or full face-piece supplied air respirator operated in pressure demand or other positive pressure mode.
Individual protection measures, such as personal protective equipment	
Eye and face protection	When handling very small quantities of the material eye protection may not be required. For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs: • Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] • Face shield. Full face shield may be required for supplementary but never for primary protection of eyes. • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. • Rubber gloves (nitrile or low-protein, powder-free latex, latex/ nitrile). Employees allergic to latex gloves should use nitrile gloves in preference. • Double gloving should be considered. • PVC gloves. • Change gloves frequently and when contaminated, punctured or torn. • Wash hands immediately after removing gloves. • Protective shoe covers. [AS/NZS 2210] • Head covering.
Body protection	See Other protection below
Other protection	• For quantities up to 500 grams a laboratory coat may be suitable. • For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs. • For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers. • For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection. • Eye wash unit. • Ensure there is ready access to an emergency shower.

Continued...

	• For Emergencies: Vinyl suit

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear to Semi-Transparent

Physical state	Liquid	**Relative density (Water = 1)**	Not Available
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**Total VOC %w/w**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	• Unstable in the presence of incompatible materials. • Product is considered stable. • Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.

Continued...

j) Aspiration Hazard	Based on available data, the classification criteria are not met.
Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Use of blood and related products can cause infection and immune reactions. Aerosols containing blood may contain the risk of infection to AIDS, hepatitis and other infectious diseases.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Exposure to long-acting anticoagulants (blood-thinning medications) has been associated with a severe bleeding disorder. The most frequent symptoms arising from ingestion of anticoagulants include bleeding into the skin, blood in the urine, passage of dark-coloured, tar-like stools due to the presence of blood altered by the intestinal juices or passage of bloody stools, easy bruising, internal bleeding, nose-bleed and gum bleeding. Polysaccharides are not easily absorbed from the digestive tract, but may produce a laxative effect. Larger doses may produce intestinal or stomach blockage. <
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Blood and blood-related products can cause the transmission of pathogens and bring up immune reactions. Workers may be exposed to AIDS, hepatitis and other infectious diseases.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Studies indicate that diets containing large amounts of non-absorbable polysaccharides, such as cellulose, might decrease absorption of calcium, magnesium, zinc and phosphorus.

Atera Block and Stain Buffer	TOXICITY	IRRITATION
	Not Available	Not Available

heparin	TOXICITY	IRRITATION
	Oral (Rat) LD50: 1950 mg/kg [2]	Not Available

sorbitan monolaurate, ethoxylated	TOXICITY	IRRITATION
	Dermal (Guinea Pig) LD50: >3000 mg/kg [1]	Eye: no adverse effect observed (not irritating) [1]
	Inhalation (Rat) LC50: >5.1 mg/l4h [1]	Skin (Human): 15mg/3D - Mild
	Oral (Mouse) LD50; >33000 mg/kg [2]	Skin: no adverse effect observed (not irritating) [1]

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Atera Block and Stain Buffer	The mainstay of secondary prevention of ischaemic stroke is the addition of medical therapy with antithrombotic agents to control the risk factors for stroke. Antithrombotic therapy is associated with significant medical complications, particularly bleeding. Side effects include · increased bruising · red or pink colored urine · stools that are bloody or look like coffee grounds · more bleeding than normal during the menstrual period · purple toes · pain, change in temperature, or blackish areas in your fingers, toes, hands, or feet
sorbitan monolaurate, ethoxylated	The Cosmetic Ingredient Review (CIR) Expert Panel concluded that listed polysorbates are safe in cosmetics when formulated to be non-irritating. This conclusion supersedes the conclusion reached in the 1984, 2000, and 2001 CIR safety assessments. This safety assessment combines polysorbates reviewed in 3 previous safety assessments with other polysorbates that have not been reviewed by the CIR Panel into a group of 80 polyethoxylated sorbitan or sorbitol esters of fatty acid. Following oral administration of polysorbate 20 to rats, ester bonds of polysorbates are hydrolyzed within the digestive tract by pancreatic lipase.24 Free fatty acids were absorbed from the digestive tract and oxidized and excreted, mainly as carbon dioxide in exhaled breath. No migration of the polyoxyethylene sorbitan into the thymus lymph nodes has been demonstrated. No sex difference has been detected in the disposition of polysorbates in rats. Following oral ingestion of polysorbate 20 in humans, 90% or more of the administered substance was excreted in the feces as metabolites, with the polyoxyethylene sorbitan structure maintained, and 2%-3% of these metabolites were excreted in the urine The Panel considered the data available to characterize the potential for polysorbates to cause systemic toxicity, irritation, sensitization, reproductive and developmental toxicity, and genotoxicity. They noted the lack of systemic toxicity at low and moderate doses in several acute and repeated-dose oral exposure studies, and low toxicity at high doses; little or no irritation or sensitization in multiple tests of dermal and ocular exposure; the absence of genotoxicity in multiple Ames tests and chromosome aberration tests, and minimal irritation and lack of sensitization in tests of dermal exposure at concentration of use. The Panel recognizes that there are data gaps regarding use and concentration of these ingredients. However, the overall information available on the types of products in which these ingredients are used, concentrations of use and the similar pattern of use raise no safety concerns. The Panel note that polysorbate 20, polysorbate 65, and polysorbate 80 were shown to enhance dermal drug absorption. The Panel cautions that care should be taken in formulating cosmetic products that may contain these ingredients in combination with any ingredients whose safety was based on their lack of dermal absorption, or when dermal absorption was a concern. Especially, care should be taken when creating formulations intended for use on infants. To address the possible presence of 1,4-dioxane and ethylene oxide impurities in these ingredients, the Panel stressed that the cosmetics industry should continue to use the necessary procedures to limit these impurities from the PEG ingredients before blending them into cosmetic formulations. The Panel expressed concern about pesticide residues and heavy metals that may be present in botanical (ie, coconut-derived) ingredients. They stressed that the cosmetics industry should continue to use current good manufacturing practices (cGMPs) to limit impurities. Data from the 1984 safety assessment suggested that polysorbates caused a slight enhancement of tumor development caused by 7,12-dimethyl-benz[a]anthracene (DMBA) and N-methyl-N -nitro-N-nitrosoguanidine (MNNG); however, the data were not consistent. For other compounds, the tumorigenic properties of 3-methyl-cholanthrene (MCA) and 3,4-benz[a]pyrene (BP) were not enhanced by polysorbates. Since the tumor enhancement effects were inconsistent and depended on the simultaneous exposure to strong chemical carcinogens, which are not present in cosmetics, the Panel felt that the weak tumor enhancement effects were not relevant to cosmetic formulations. Because some studies showed minimal irritation at concentrations that are used in cosmetics, the Panel cautioned that products containing these ingredients should be formulated to be non-irritating. It was noted that at the time of the 2001 safety assessment on sorbeth beeswaxes, the Panel had recommended that cosmetic formulations containing PEGs not be used on damaged skin because of the possibility of renal toxicity when PEGs were applied to severely damaged skin, such as in burn patients. Since then, PEGs have been re-reviewed and the additional data demonstrated minimal dermal penetration of low-molecular weight PEGs. The amount of PEGs that would penetrate the stratum corneum barrier, even if damaged,

Continued...

	from the use of cosmetics was well below the level of renal toxicity. Therefore, the Panel has removed the caveat that PEGs should not be used on damaged skin. The Panel strongly asserted that it is inappropriate to apply cosmetic products containing high concentrations of PEGs to individuals exhibiting barrier skin disruption through both the stratum corneum and the epidermis. The Panel discussed the issue of incidental inhalation exposure from spray products, including aerosol and pump hair sprays, spray deodorants, spray body and hand products, and spray moisturizing products. The limited acute exposure data available from 1 new inhalation study and 1 historical tracheal study suggest little potential for respiratory effects at relevant doses. These ingredients are reportedly used at concentrations up to 4% in cosmetic products that may be aerosolized. The Panel noted that 95%-99% of droplets/particles would not be respirable to any appreciable amount. Coupled with the small actual exposure in the breathing zone and the concentrations at which the ingredients are used, the available information indicates that incidental inhalation would not be a significant route of exposure that might lead to local respiratory or systemic effects. Safety Assessment of Polysorbates as Used in CosmeticJuly 2015 https://www.cir-safety.org/sites/default/files/PSorba_062015_FR_0.pdf For sorbitan esters, ethoxylated (syn: polyoxyethylene sorbitan esters): Some of the early short-term studies with these polyoxyethylene sorbitan esters in rats and hamsters showed deleterious effects. Subsequent work suggests that these were largely due to diarrhoea resulting from a large amount of unabsorbed polyglycol, possibly aggravated in some experiments by the use of an unsuitable basal diet. Since that time there has been considerable improvement in testing procedures,and more extensive long-term studies have been carried out. It seems reasonable therefore to base the evaluation of these substances on the levels causing no adverse effects indicated by the results of the more recent investigations. The significance of the local tumours which were produced by injection has been discussed at the meeting of the Scientific Group (1966). No increase in tumour incidence has followed the oral intake of polyoxyethylene sorbitan esters. Furthermore, large doses of the oleate and stearate have been well tolerated by human subjects. Polyoxyethylene (20) sorbitan monoester of lauric, oleic, palmitic and stearic acid and triester of stearic acid Seventeenth Report of the Joint FAO/WHO Expert Committee on Food Additives, Wld Hlth Org. Techn. Rep. Ser., 1974, No. 539; FAO Nutrition Meetings Report Series, 1974, No. 53. Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products. Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation. The sorbitan esters are agents that typically find use as emulsifiers, stabilizers, and thickeners in foods, cosmetics and medical products. They do not represent a toxicological concern since they are derived from naturally occurring materials and are ultimately metabolised back to these same natural constituents. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
Atera Block and Stain Buffer & heparin	The most common side-effects of low molecular weight heparin (LMWHs) include bleeding, which could be severe or even fatal, allergic reactions, injection site reactions, and increases in liver enzyme tests, usually without symptoms. The use of heparin and LMWHs can sometimes be complicated by a decrease in platelet count, a complication known as Heparin Induced Thrombocytopenia.13 Two forms have been described: a clinically benign, non-immune and reversible form (Type I) and a rare, more serious immune-mediated form or Type II. HIT Type II is caused by the formation of auto antibodies that recognize complexes between heparin and platelet factor 4 (PF4) and is therefore associated with a substantial risk of thrombotic complications. The incidence is difficult to estimate but may reach up to 5% of patients treated with unfractionated heparin (UFH) or about 1% with LMWH.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ *– Data either not available or does not fill the criteria for classification*
✓ *– Data available to make classification*

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Atera Block and Stain Buffer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
heparin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
sorbitan monolaurate, ethoxylated	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96h	Fish	383mg/l	2
Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data***				

Sugar-based compounds (saccharides), including polysaccharides are generally easily decomposed by biodegradation. Not all polysaccharides decompose with equal rapidity, and polysaccharides are also synthesised by microorganisms during, for example, the compost maturation phases. Water-insoluble species such as cellulose take longer to decompose and those with a significant degree of branching also take longer.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
sorbitan monolaurate, ethoxylated	LOW (LogKOW = -2.03)

Continued...

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: • Reduction • Reuse • Recycling • Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. • **DO NOT** allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Recycle wherever possible or consult manufacturer for recycling options. • Consult State Land Waste Authority for disposal. • Bury or incinerate residue at an approved site. • Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
heparin	Not Applicable
sorbitan monolaurate, ethoxylated	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
heparin	Not Applicable
sorbitan monolaurate, ethoxylated	Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

HEPARIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

- Not Applicable

SORBITAN MONOLAURATE, ETHOXYLATED IS FOUND ON THE FOLLOWING REGULATORY LISTS

- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US EPA Pesticide Chemical Search - Conventional Chemical

Additional Regulatory Information

Not Applicable

Federal Regulations

Continued...

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

Additional Federal Regulatory Information

Not Available

US. EPCRA SECTION 313 TOXIC RELEASE INVENTORY (TRI) (40 CFR 372)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

Additional State Regulatory Information

Not Available

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (heparin, sorbitan monolaurate, ethoxylated)
China - IECSC	No (heparin)
Columbia - Columbia National Industrial Chemicals Inventory	No (heparin, sorbitan monolaurate, ethoxylated)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (heparin)
Korea - KECI	No (heparin)
New Zealand - NZIoC	Yes
Philippines - PICCS	No

Continued...

	(heparin)
USA - TSCA	TSCA Inventory 'Active' substance(s) (sorbitan monolaurate, ethoxylated); No (heparin)
Taiwan - TCSI	Yes
Mexico - INSQ	No (heparin)
Vietnam - NCI	No (heparin)
Russia - FBEPH	No (heparin, sorbitan monolaurate, ethoxylated)
UAE - Control List (Banned/Restricted Substances)	No (heparin, sorbitan monolaurate, ethoxylated)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 OTHER INFORMATION

Revision Date	25/06/2026
Initial Date	04/06/2026

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

end of SDS

Atera Multi-Tissue Stain

10x Genomics, Inc.

Part Number: **2001946**
Version No: **1.1**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **03/07/2026**
Revision Date: **03/07/2026**
Print Date: **03/07/2026**
S.GHS.USA.EN.B

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Atera Multi-Tissue Stain
Synonyms	Not Available
Other means of identification	2001946

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Professional Users Only

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**10x Genomics, Inc.**
Address	6230 Stoneridge Mall Rd, Pleasanton, California, 94588, United States of America
Telephone	+1 925 401 7300
Fax	NA
Website	www.10xgenomics.com
Email	info@10xgenomics.com

Emergency phone number

Association / Organisation	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	**+49 32 211121704**
Other emergency telephone number(s)	**+61 3 9573 3188**

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

Classification	Non hazardous

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Page 1 continued...

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name

Ingredients hidden by Auto Sanitise option as they are non-hazardous.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: • Immediately remove all contaminated clothing, including footwear. • Flush skin and hair with running water (and soap if available). • Seek medical attention in event of irritation.
Inhalation	• If fumes, aerosols or combustion products are inhaled remove from contaminated area. • Other measures are usually unnecessary.
Ingestion	• **IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.** • For advice, contact a Poisons Information Centre or a doctor. • Urgent hospital treatment is likely to be needed. • In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. • If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. • If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. **Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:** • **INDUCE** vomiting with fingers down the back of the throat, **ONLY IF CONSCIOUS**. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. **NOTE:** Wear a protective glove when inducing vomiting by mechanical means.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).
For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- **DO NOT** use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.

Continued...

- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	• Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves in the event of a fire. • Prevent, by any means available, spillage from entering drains or water courses. • Use fire fighting procedures suitable for surrounding area. • **DO NOT** approach containers suspected to be hot. • Cool fire exposed containers with water spray from a protected location. • If safe to do so, remove containers from path of fire. • Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	• Non combustible. • Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	• Clean up all spills immediately. • Avoid breathing vapours and contact with skin and eyes. • Control personal contact with the substance, by using protective equipment. • Contain and absorb spill with sand, earth, inert material or vermiculite. • Wipe up. • Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • Stop leak if safe to do so. • Contain spill with sand, earth or vermiculite. • Collect recoverable product into labelled containers for recycling. • Neutralise/decontaminate residue (see Section 13 for specific agent). • Collect solid residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. • If contamination of drains or waterways occurs, advise emergency services.

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	• Avoid skin contact, including inhalation. • Wear protective clothing when risk of exposure occurs. • Use in a well-ventilated area. • Avoid contact with moisture. • Avoid contact with incompatible materials. • When handling, **DO NOT** eat, drink or smoke. • Keep containers securely sealed when not in use. • Avoid physical damage to containers. • Always wash hands with soap and water after handling. • Work clothes should be laundered separately. Launder contaminated clothing before re-use. • Use good occupational work practice. • Observe manufacturer's storage and handling recommendations contained within this SDS. • Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. • **DO NOT** allow clothing wet with material to stay in contact with skin
Other information	

Continued...

Conditions for safe storage, including any incompatibilities

Suitable container	• Polyethylene or polypropylene container. • Packing as recommended by manufacturer. • Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	TEEL-1	TEEL-2	TEEL-3
Atera Multi-Tissue Stain	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Atera Multi-Tissue Stain	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Continued...

	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	• Overalls. • P.V.C apron. • Barrier cream. • Skin cleansing cream. • Eye wash unit.

Respiratory protection

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear		
Physical state	Liquid	**Relative density (Water = 1)**	Not Available
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**Total VOC %w/w**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

Continued...

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	• Unstable in the presence of incompatible materials. • Product is considered stable. • Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Atera Multi-Tissue Stain	TOXICITY	IRRITATION
	Not Available	Not Available
Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***	

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ *– Data either not available or does not fill the criteria for classification*
✓ *– Data available to make classification*

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Atera Multi-Tissue Stain	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data***				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Continued...

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	• Containers may still present a chemical hazard/ danger when empty. • Return to supplier for reuse/ recycling if possible. Otherwise: • If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. • Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: • Reduction • Reuse • Recycling • Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. • **DO NOT** allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Recycle wherever possible. • Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. • Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). • Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Continued...

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

Additional Federal Regulatory Information

Not Available

US. EPCRA SECTION 313 TOXIC RELEASE INVENTORY (TRI) (40 CFR 372)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

Additional State Regulatory Information

Not Available

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	Yes
China - IECSC	Yes
Columbia - Columbia National Industrial Chemicals Inventory	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes

Continued...

Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	Yes
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 OTHER INFORMATION

Revision Date	03/07/2026
Initial Date	03/07/2026

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

end of SDS

Atera Signal Booster

10x Genomics, Inc.

Part Number: **2001947**
Version No: **2.7**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **09/06/2026**
Revision Date: **04/08/2026**
Print Date: **04/08/2026**
S.GHS.USA.EN.B

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Atera Signal Booster
Synonyms	Not Available
Other means of identification	2001947

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Professional Users Only

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**10x Genomics, Inc.**
Address	6230 Stoneridge Mall Rd, Pleasanton, California, 94588, United States of America
Telephone	+1 925 401 7300
Fax	NA
Website	www.10xgenomics.com
Email	info@10xgenomics.com

Emergency phone number

Association / Organisation	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	**+49 32 211121704**
Other emergency telephone number(s)	**+61 3 9573 3188**

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

Classification	Non hazardous

Label elements

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Page 1 continued...

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name

Ingredients hidden by Auto Sanitise option as they are non-hazardous.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: • Immediately remove all contaminated clothing, including footwear. • Flush skin and hair with running water (and soap if available). • Seek medical attention in event of irritation.
Inhalation	• If fumes, aerosols or combustion products are inhaled remove from contaminated area. • Other measures are usually unnecessary.
Ingestion	• Immediately give a glass of water. • First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	• Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves in the event of a fire. • Prevent, by any means available, spillage from entering drains or water courses. • Use fire fighting procedures suitable for surrounding area. • **DO NOT** approach containers suspected to be hot. • Cool fire exposed containers with water spray from a protected location. • If safe to do so, remove containers from path of fire. • Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	• Non combustible. • Not considered a significant fire risk, however containers may burn. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

Continued...

See section 12

Methods and material for containment and cleaning up

Minor Spills	• Clean up all spills immediately. • Avoid breathing vapours and contact with skin and eyes. • Control personal contact with the substance, by using protective equipment. • Contain and absorb spill with sand, earth, inert material or vermiculite. • Wipe up. • Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • Stop leak if safe to do so. • Contain spill with sand, earth or vermiculite. • Collect recoverable product into labelled containers for recycling. • Neutralise/decontaminate residue (see Section 13 for specific agent). • Collect solid residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. • If contamination of drains or waterways occurs, advise emergency services.

Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	• Avoid skin contact, including inhalation. • Wear protective clothing when risk of exposure occurs. • Use in a well-ventilated area. • Avoid contact with moisture. • Avoid contact with incompatible materials. • When handling, **DO NOT** eat, drink or smoke. • Keep containers securely sealed when not in use. • Avoid physical damage to containers. • Always wash hands with soap and water after handling. • Work clothes should be laundered separately. Launder contaminated clothing before re-use. • Use good occupational work practice. • Observe manufacturer's storage and handling recommendations contained within this SDS. • Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. • **DO NOT** allow clothing wet with material to stay in contact with skin
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	• Polyethylene or polypropylene container. • Packing as recommended by manufacturer. • Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	TEEL-1	TEEL-2	TEEL-3
Atera Signal Booster	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Atera Signal Booster	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. Type of Contaminant: | Air Speed:

Continued...

	solvent, vapours, degreasing etc., evaporating from tank (in still air) — 0.25-0.5 m/s (50-100 f/min)
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) — 0.5-1 m/s (100-200 f/min.)
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) — 1-2.5 m/s (200-500 f/min)
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). — 2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
· frequency and duration of contact,
· chemical resistance of glove material,
· glove thickness and
· dexterity
Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
· Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:
· Excellent when breakthrough time > 480 min
· Good when breakthrough time > 20 min
· Fair when breakthrough time < 20 min
· Poor when glove material degrades
For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Continued...

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available

Physical state	Liquid	**Relative density (Water = 1)**	Not Available
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**Total VOC %w/w**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	• Unstable in the presence of incompatible materials. • Product is considered stable. • Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has **NOT** been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Continued...

	TOXICITY	IRRITATION
Atera Signal Booster	Not Available	Not Available
Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***	

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✔ ***– Data available to make classification***

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Atera Signal Booster	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data***				

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: • Reduction • Reuse • Recycling • Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. • **DO NOT** allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Recycle wherever possible. • Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. • Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). • Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO

Continued...

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

Additional Regulatory Information

Not Applicable

ECHA SUMMARY

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

Additional Federal Regulatory Information

Not Available

US. EPCRA SECTION 313 TOXIC RELEASE INVENTORY (TRI) (40 CFR 372)

None Reported

State Regulations

Continued...

US. CALIFORNIA PROPOSITION 65

None Reported

Additional State Regulatory Information

Not Available

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	Yes
China - IECSC	Yes
Columbia - Columbia National Industrial Chemicals Inventory	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	Yes
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 OTHER INFORMATION

Revision Date	04/08/2026
Initial Date	09/06/2026

SDS Version Summary

Version	Issue Date	Sections Updated
1.7	04/08/2026	Physical and chemical properties - Physical Properties

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

end of SDS